

4x4-4x6-5x6
10' Tower Assembly Instructions

Notes:

(Do not tighten nuts until tower is fully assembled)
All Diagonals will connect to the outside of Vertical Legs
All Horizontals will connect to the inside of Vertical Legs

- (A) Position Base on side
- (B) Attach (4) 10' Legs to inside of Base Legs
- (C) Attach HB4FT5 Horizontal Braces (see diagram) angle down to the inside of Vertical Legs. (you will need to remove nut from bolt and reattach after connecting brace)
- (D) Attach HB4FT10 Horizontal Braces (see diagram) angle down to inside of Vertical Legs. (you will need to remove nut from bolt and reattach after connecting brace)
- (E) Attach DB4FT10 Diagonals (see diagram) outside legs (you will need to remove nut from bolt and re-attach after connecting brace)
- (F) Tighten all nuts using ½" wrench, ratchet and socket
- (G) Attach Handrail using 2" bolts and 5/16" nuts at side of porch
- (H) Attach Blind to Tower using supplied bolt kit.
- (I) Stand Blind and Tower in standing position
- (J) Attach Stairway to slots at Porch end.
- (K) Attach Stairway Handrail to Stairway using stairway brackets

We hope you have many happy and enjoyable hours hunting from your "**Superior**" Blind.

If further instructions are needed please call (940) 683-4792 or you local dealer.

HAPPY HUNTING!!!!!!