

4x4-4x6-5x6
15' Tower Assembly Instructions

Notes:

(Do not tighten nuts until tower is fully assembled)
All Diagonals will connect to the outside of Vertical Legs
All Horizontals will connect to the inside of Vertical Legs

- (A) Position Base on side
- (B) Attach (4) 15' Legs to inside of Base Legs
- (C) Attach HB4FT5 Horizontal Braces (see diagram) angle down to the inside of Vertical Legs.
- (D) Attach HB4FT10 Horizontal Braces (see diagram) angle down to inside of Vertical Legs.
- (E) Attach HB4FT15 Horizontal Braces (see diagram) angle down to inside of Vertical Legs.
- (F) Attach DB4FT15 Diagonal Braces (see diagram) angle down to the outside of vertical legs. (you will need to remove nuts and bolts and reattach after installing each diagonal brace)
- (G) Attach DB4FT10 Diagonal Braces (see diagram) angle down to the outside of vertical legs. (you will need to remove nuts and bolts and reattach after installing each diagonal brace)
- (H) Tighten all nuts using ½" wrench, ratchet and socket
- (I) Attach Porch Handrail using 2" bolts and 5/16" nuts at side of porch
- (J) Attach Blind to Tower using supplied bolt kit.
- (K) Stand Blind and Tower in standing position
- (L) Attach Stairway to slots at Porch end.
- (M) Attach 15' Stairway Handrail to Stairway using stairway brackets.

We hope you have many happy and enjoyable hours hunting
from your "*Superior*" Blind.
If further instructions are needed please call, (940) 683-4792 or
you local dealer.

HAPPY HUNTING!!!!!!